

Form PTO-1390		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER P21105
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			U.S. APPLICATION NO. (If known, see 37 CFR 1.5) <b>09/857171</b>
INTERNATIONAL APPLICATION NO. PCT/SG99/00009	INTERNATIONAL FILING DATE 22 February 1999	PRIORITY DATE CLAIMED 16 December 1998	
TITLE OF INVENTION A METHOD OF DETACHING AND RE-ATTACHING COMPONENTS OF A COMPUTING PROCESS			
APPLICANT(S) FOR DO/EO/US Hwee Hwa PANG and Teow Hin NGAIR			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information.			
1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This is an express request to promptly begin national examination procedures (35 U.S.C. 371(f)). 4. <input checked="" type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (PCT Article 31). 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. <input checked="" type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> has been communicated by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371 (c)(2)). 7. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> have been communicated by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)) 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). "Executed" 10. <input type="checkbox"/> An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (U.S.C. 371(c)(5)).			
<b>Items 11 to 16 below concern other document(s) or information included:</b>			
11. Assignee: <u>KENT RIDGE DIGITAL LABS of SINGAPORE</u>			
12. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.			
13. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.			
14. <input checked="" type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment.			
15. <input type="checkbox"/> A substitute specification.			
16. <input type="checkbox"/> A change of power of attorney and/or address letter.			
17. <input type="checkbox"/> Figure of Drawing to be published _____			
18. <input checked="" type="checkbox"/> Other items or information: Cover Sheet and International Application as published. PCT/ISA/210. Claim of Priority.			

U.S. APPLICATION NO. 1.5) <b>09/857171</b>		INTERNATIONAL APPLICATION NO. PCT/SG99/00009		ATTORNEY'S DOCKET NUMBER P21105	
19. The following fees are submitted:  Basic National Fee (37 CFR 1.492(a)(1)-(5)): Search report has been prepared by the EPO or JPO. . . . . \$ 860.00 International preliminary examination fee paid to USPTO (37 CFR 1.482). . . . . \$ 690.00 No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO(37 CFR 1.445(a)(2)). . . . . \$ 710.00 Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2) paid to USPTO. . . . . \$1,000.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4). . . . . \$ 100.00  ENTER APPROPRIATE BASIC FEE AMOUNT =				CALCULATIONS	PTO USE ONLY
				\$860.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than 20 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
Claims	Number Filed	Number Extra	RATE		
Total Claims	22 - 20 =	2	X \$18.00	\$36.00	
Independent Claims	1 - 3 =	0	X \$80.00	\$0.00	
Multiple dependent claim(s) (if applicable)			+ \$270.00	\$0.00	
TOTAL OF ABOVE CALCULATIONS =				\$896.00	
Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				\$	
SUBTOTAL =				\$896.00	
Processing fee of \$130.00 for furnishing the English translation later than 20 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				+	
Extension of Time fee in the amount of \$					
TOTAL NATIONAL FEE =				\$896.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				+	\$40.00
TOTAL FEES ENCLOSED =				\$936.00	
				Amount to be refunded	\$
				Charged	\$
a. <input checked="" type="checkbox"/> A check in the amount of \$936.00 to cover the above fees is enclosed.					
b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$_____ to cover the above fees.					
c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 19-0089.					
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.					
SEND ALL CORRESPONDENCE TO CUSTOMER NO. 7055 AT THE PRESENT ADDRESS OF: Bruce H. Bernstein GREENBLUM & BERNSTEIN, P.L.C. 1941 Roland Clarke Place Reston, VA 20191 (703) 716-1191					
				SIGNATURE Bruce H. Bernstein NAME 33,329	
				29,027 REGISTRATION NUMBER	

P21105.A01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Hwee Hwa PANG and Teow Hin NGAIR  
Serial No : Not Yet Assigned (National Stage of PCT/SG99/00018)  
Filed : Concurrently Herewith (International Filing Date March 18, 1999)  
For : A METHOD FOR DETACHING AND RE-ATTACHING COMPONENTS  
OF A COMPUTING PROCESS

**PRELIMINARY AMENDMENT**

Commissioner of Patents and Trademarks  
Washington, D.C. 20231

Sir:

Prior to calculation of the filing fees and the examination of the above-identified patent application on the merits, the Examiner is respectfully requested to amend the claims as follows:

IN THE CLAIMS

Please amend the claims as follows (a marked-up copy of the claim amendments is provided as an attachment to this Amendment):

3. (Amended-Clean Text) A method as claimed in claim 1 wherein a construct is formed for storing said sub-process, while said first process retains the process identity of said computing process.

6. (Amended-Clean Text) A method as claimed in claim 3 wherein said construct is provided with and authorising signature.

7. (Amended-Clean Text) A method as claimed in claim 3 wherein said construct is sent to a memory storage device.

8. (Amended-Clean Text) A method as claimed in claim 3 wherein said sub-process is a dormant process comprising data, program code and execution states of said computing process temporarily not required by said first process, and wherein said first process is able to re-acquire data, program codes and execution states from said dormant process as and when required by said first process.

10. (Amended-Clean Text) A method as claimed in claim 8 wherein said sub-process comprises data, program code and execution states specific to a given user of a computing means, and wherein said second process is formed to temporarily store said data, program code and execution states while said user is absent from said computing means.

11. (Amended-Clean Text) A method as claimed in claim 3 wherein after said first process finishes executing data, program modules and execution states from said first process are added to said sub-process and said sub-process is reactivated.

13. (Amended-Clean Text) A method as claimed in claim 1 wherein a construct is formed for storing said sub-process, while said first process is run in place of said computing process.

16. (Amended-Clean Text) A method as claimed in claim 13 wherein said construct is provided with and authorising signature.

17. (Amended-Clean Text) A method as claimed in claim 13 wherein said construct is sent to a memory storage device.

18. (Amended-Clean Text) A method as claimed in claim 13 wherein said sub-process is a dormant process comprising data, program code and execution states of said computing process temporarily not required by said first process, and wherein said first process is able to re-acquire data, program codes and execution states from said dormant process as and when required by said first process.

20. (Amended-Clean Text) A method as claimed in claim 18 wherein said sub-process comprises data, program code and execution states specific to a given user of a computing means, and wherein said second process is formed to temporarily store said data, program code and execution states while said user is absent from said computing means.

P21105.A01

21. (Amended-Clean Text) A method as claimed in claim 13 wherein after said first process finishes executing data, program modules and execution states from said first process are added to said sub-process and said sub-process is reactivated.

REMARKS

By the above amendment, the claims have been amended to delete multiple dependency.

If there should be any questions, the Examiner is invited to contact the undersigned at the telephone number listed below.

Respectfully submitted,  
Teow Hin NGAIR et al.

---

Bruce H. Bernstein  
Reg. No. 29,027

June 12, 2001  
GREENBLUM & BERNSTEIN, P.L.C.  
1941 Roland Clarke Place  
Reston, VA 20191  
(703) 716-1191

P21105.A01

21. (Amended-Clean Text) A method as claimed in claim 13 wherein after said first process finishes executing data, program modules and execution states from said first process are added to said sub-process and said sub-process is reactivated.

REMARKS

By the above amendment, the claims have been amended to delete multiple dependency.

If there should be any questions, the Examiner is invited to contact the undersigned at the telephone number listed below.

Respectfully submitted,  
Hwee Hwa PANG and Teow Hin NGAIR

---

Bruce H. Bernstein  
Reg. No. 29,027

June 15, 2001  
GREENBLUM & BERNSTEIN, P.L.C.  
1941 Roland Clarke Place  
Reston, VA 20191  
(703) 716-1191

MARKED-UP COPY OF AMENDED CLAIMS

3. (Amended) A method as claimed in claim 1 [or 2] wherein a construct is formed for storing said sub-process, while said first process retains the process identity of said computing process.

6. (Amended) A method as claimed in claim 3 [any of claims 3 to 5] wherein said construct is provided with and authorising signature.

7. (Amended) A method as claimed in claim 3 [any of claims 3 to 6] wherein said construct is sent to a memory storage device.

8. (Amended) A method as claimed in claim 3 [any of claims 3 to 7] wherein said sub-process is a dormant process comprising data, program code and execution states of said computing process temporarily not required by said first process, and wherein said first process is able to re-acquire data, program codes and execution states from said dormant process as and when required by said first process.

10. (Amended) A method as claimed in claim 8 [or 9] wherein said sub-process comprises data, program code and execution states specific to a given user of a computing means, and wherein said second process is formed to temporarily store said data, program code and execution states while said user is absent from said computing means.



11. (Amended) A method as claimed in claim 3 [any of claims 3 to 10] wherein after said first process finishes executing data, program modules and execution states from said first process are added to said sub-process and said sub-process is reactivated.

13. (Amended) A method as claimed in claim 1 [or 2] wherein a construct is formed for storing said sub-process, while said first process is run in place of said computing process.

16. (Amended) A method as claimed in claim 13 [any of claims 13 to 15] wherein said construct is provided with and authorising signature.

17. (Amended) A method as claimed in claim 13 [any of claims 13 to 16] wherein said construct is sent to a memory storage device.

18. (Amended) A method as claimed in claim 13 [any of claims 13 to 17] wherein said sub-process is a dormant process comprising data, program code and execution states of said computing process temporarily not required by said first process, and wherein said first process is able to re-acquire data, program codes and execution states from said dormant process as and when required by said first process.

P21105.A01

20. (Amended) A method as claimed in claim 18 [or 19] wherein said sub-process comprises data, program code and execution states specific to a given user of a computing means, and wherein said second process is formed to temporarily store said data, program code and execution states while said user is absent from said computing means.

21. (Amended) A method as claimed in claim 13 [any of claims 13 to 20] wherein after said first process finishes executing data, program modules and execution states from said first process are added to said sub-process and said sub-process is reactivated.

A METHOD FOR DETACHING AND RE-ATTACHING  
COMPONENTS OF A COMPUTING PROCESS

This invention relates to a method for detaching and re-attaching components of a  
5 computing process, and in particular for example to such a method for removing parts of  
the data, program code and execution state of a process and for transferring those parts to  
secondary or tertiary storage where they may be stored while not needed, before being re-  
attached to the process when required once more.

In a number of computing environments a large number of processes may be  
10 running concurrently on a single machine. This can happen for example in a follow-me  
computing environment where processes can span multiple user sessions. This results in a  
large number of processes – some active, some suspended – on a single machine. The  
presence of such a large number of concurrent processes can place a heavy burden on the  
resources of the system and can substantially slow down the running speed of the system.

A similar problem can occur in networks involving computing devices that may  
15 have limited memory space. Unless the memory space of such devices is used with  
maximum efficiency, the memory can quickly become overloaded. Minimizing resource  
usage is therefore imperative.

It would therefore be desirable if it were possible for elements of a computing  
20 process that were temporarily not required to be removed from the limited device or  
network and stored in such a way that they could be re-integrated into the process at a  
later time when required.

Recent years have seen a number of developments in computing science  
regarding how elements within a software application are treated and handled. In this  
25 context the most basic elements to be found within a software application are data and  
program modules. Traditional procedural programming paradigms focus on the logic of  
the software application, so a program is structured based on program modules. One uses  
the program modules by explicitly supplying to them the data on which they should  
operate.

30 More recently there has been a move towards an object-oriented paradigm. In this  
paradigm, programs are structured around objects, with each object representing an entity

in the world being modeled by the software application. Each object manages its own data (state), which are hidden from the external world (other objects and programs). An object in a program interacts with another object by sending it a message to invoke one of its exposed program modules (method). This paradigm imposes better control and protection over internal data, and helps to structure complex applications designed and implemented by a team of programmers. An example of an object-oriented environment can be found in US 5,603,031. This discloses an environment in which new agents (essentially objects) consisting of data and program modules can be sent between machines. However, in the environment of US 5,603,031 a special application code is needed to convert state information into data in the newly created process, and to ensure that the latter begins execution from the right instruction. Since execution state cannot be manipulated directly, it is very tedious, if not impossible, to transfer shared resources within a process to a surrogate. Moreover since the surrogate has a different identity from the original process, shared resources managed externally, such as data locks, cannot be transferred.

While object-oriented paradigm represents a significant advance in software engineering, the data and modules that constitute each object are static. The paradigm is still inadequate for writing programs that must evolve during execution, eg programs that need to pick up, drop, or substitute selected modules. There have been several attempts at overcoming this limitation. For example, work described in US Patents 4954941, 5175828, 5339430 and 5659751 address techniques for re-linking or re-binding selected software modules dynamically during runtime. Also Microsoft's Win32 provides for explicit mapping and un-mapping of dynamic linked libraries into the address space of a process through the LoadLibrary and FreeLibrary calls. With this prior art, however, the prototype or specification of functions and symbols are fixed beforehand and compiled into application programs. This enables a process to mutate into and back from a surrogate by replacing selected program modules. However, the replacement modules must retain the same function prototypes making coding complicated and unnatural. Also data structures that are not needed by the surrogate remain in memory.

Work has also been done in the area of process checkpointing and recovery. This deals with mechanisms for preserving process state and recovery from machine crashes.

The mechanisms operate from outside of the process and the process remains the same upon resumption.

In this specification the following terms will be used with the following meaning:

"First class entity": an object that can be manipulated directly.

5 "Process": a combination of data, program module(s) and current execution state.

"Execution state": the values and contents of transient parameters such as the contents of registers, frames, counters, look-up tables and the like.

According to the present invention there is provided a method for removing a part of a computing process, wherein said process splits into a first process and a sub-process, the sub-process comprising items of data and/or program code and/or execution states of said computing process temporarily not required by said first process.

By means of this arrangement a process is enabled to temporarily or permanently detach from itself sub-processes comprising subsets of the data, program code and execution states of the process, and to remove the sub-process to, for example, secondary or tertiary storage until they are needed again. This compacts the size of the process, freeing up resources for other processes. If the sub-process is not required again it may be discarded completely. The sub-process may comprise only data, or only program code or only execution state information, or any combination of these three components.

The method of the present invention may be implemented by two approaches. In a first approach the process splits into a first process and sub-processes with the first process retaining the process identity of the original computing process. Alternatively, if retaining original process identity is not required, the original process may split into two new processes.

In either event the sub-process may comprise data, program code and execution states that is permanently not required and which may be deleted, or it may comprise data, program code and execution states that is only temporarily not required and which may be partially or totally re-acquired by the first process. Data, program code and execution states may be temporarily not required by the first process generally, or may be specific to a particular user of computing means who may be temporarily absent from the computing means. In either case temporarily removing the sub-process frees up resources for the first process.

The method is founded upon the ability of a process to manipulate its own data, program code and execution state directly. This ability enables a process to split itself into a first process and a second sub-process.

In a preferred embodiment a construct is formed for storing the sub-process. This  
5 construct may be formed by a construct operation that suspends all active threads of the computing process and creates a new process comprising at least some of the data and/or program modules and/or execution state of the computing process, and stores the new process in a data area of the computing process.

In a preferred embodiment the construct comprises only data, program modules  
10 and execution state falling within lists that are passed to the construct operation.

Optionally the construct may be provided with an authorising signature.

If desired, following formation of a construct storing the sub-process the construct may be sent to a memory storage device from which the construct may be retrieved when required once more.

15 While running the first process may re-acquire data, program codes and execution states from the sub-process as and when required. The first process may also load selected program modules as required.

When it is time to restore the original process, the first process may simply drop off any unwanted extraneous data, program code and execution states that it may have  
20 picked up during execution, and then merges with the sub-process to pool together their data, program code and execution states.

An embodiment of the invention will now be described by way of example and with reference to the accompanying drawings, in which:-

Fig.1 is a general schematic model of an operating environment of a computing  
25 system.

Fig.2 schematically illustrates a process life-cycle and operations that may be carried out on the process,

Fig.3 is a flowchart illustrating the hibernaculum Construct operation,

Fig.4 is a flowchart illustrating the Mutate operation,

30 Fig.5 is a flowchart illustrating the Usurp operation, and

Fig.6 is a flowchart illustrating the Bequeath operation.

Figure 1 shows the general model of a computing system. An application program 30 comprises data 10 and program modules 20. The operating system 60, also known as the virtual machine, executes the application 30 by carrying out the instructions in the program modules 20, which might cause the data 10 to be changed. The execution is effected by controlling the hardware of the underlying machine 70. The status of the execution, together with the data and results that the operating system 60 maintains for the application 30, form its execution state 40.

Such a model is general to any computing system. It should be noted here that the present invention starts from the realisation that all the information pertaining to the application at any time is completely captured by the data 10, program modules 20 and execution state 40, known collectively as the process 50 of the application 30.

The process 50 can have one or more threads of execution at the same time. Each thread executes the code of a single program module at any given time. Associated with the thread is a current context frame, which includes the following components:

- A set of registers
- A program counter, which contains the address of the next instruction to be executed
- Local variables of the module
- Input and output parameters of the module
- Temporary results of the module

In any module A, the thread could encounter an instruction to invoke another module B. In response, the program counter in the current frame is incremented, then a new context frame is created for the thread before it switches to executing module B. Upon completing module B, the new context frame is discarded. Following that, the thread reverts to the previous frame, and resumes execution of the original module A at the instruction indicated by the program counter, i.e., the instruction immediately after the module invocation. Since module B could invoke another module, which in turn could invoke some other module and so on, the number of frames belonging to a thread may grow and reduce with module invocations and completions. However, the current frame of a thread at any given time is always the one that was created last. For this

reason, the context frames of a thread are typically stored in a stack with new frames being pushed on and popped from the top. The context frames of a thread form its execution state, and the state of all the threads within the process 50 constitute its execution state 40 in Fig.1.

5 The data 10 and program modules 20 are shared among all threads. The data area is preferably implemented as a heap, though this is not essential. The locations of the data 10 and program modules 20 are summarized in a symbol table. Each entry in the table gives the name of a datum or a program module, its starting location in the address space, its size, and possibly other descriptors. Instead of having a single symbol table, each  
10 process may alternatively maintain two symbol tables, one for data alone and the other for program modules only, or the process could maintain no symbol table at all.

In a preferred embodiment of the present invention, the data and program code of a process are stored in a heap and a program area respectively and are shared by all the threads within the process. In addition the execution state of the process comprises a  
15 stack for each thread, each stack holding context frames, in turn each frame containing the registers, local variables and temporary results of a program module, as well as addresses for further module invocations and returns. Before describing an embodiment of the invention in more detail, however, it is first necessary to introduce some definitions of data types and functions that are used in the embodiment and which will be referred to  
20 further below.

In addition to conventional data types such as integers and pointer, four new data types Data, Module, Stack and Hibernaculum are defined in the present invention:

Data: A variable of this data type holds a set of data references. Members are added to  
25 and removed from the set by means of the following functions;

Int AddDatum(Data d, String dataname) inserts the data item dataname in the heap of the process as a member of d.

Int DelDatum(Data d, String dataname) removes the data item dataname from d.

30 Module: A variable of this data type holds a set of references to program modules. Members are added to and removed from the set with the following functions;



Int AddModule(Module d, String modulename) inserts the program module modulename in the program area of the process as a member of d.

5 Int DelModule(Module d, Stringname modulename) removes the program module modulename from d.

Stack: A variable of this data type holds a list of ranges of execution frames from the stack of the threads. The list may contain frame ranges from multiple threads, however no  
10 thread can have more than one range. Variables of this type are manipulated by the following functions:

Int OpenFrame(Stack d, Thread threadname) inserts into d a new range for the thread threadname, beginning with the thread's current execution frame. This  
15 function has no effect if the thread already has a range in d.

Int CloseFrame(Stack d, Thread threadname) ends the open-ended range in d that belongs to the thread threadname. This function has no effect if the thread does not currently have an open-ended range in d.

20 Int PopRange(Stack d, Thread threadname) removes from d the range belonging to the thread threadname.

Hibernaculum: A variable of this data type is used to hold a suspended process.

25 As will be explained in more detail below a process may be suspended and stored in a construct formed by the following operation:

Hibernaculum Construct(Stack s, Module m, Data d): This operation creates a new  
30 process with the execution state, program table and data heap specified as input parameters. The process is immediately suspended and then returned in a hibernaculum.

The hibernaculum may be signed by the originating process as indication of its authenticity. Fig.3 is a flow-chart showing the hibernaculum construct operation.

5 A hibernaculum may be sent between operating environments by the following send and receive functions:

Int Send(Hibernaculum h, Target t) transmits the process contained within h to the specified target.

10 Hibernaculum Receive(Source s) receives from the specified source a hibernaculum containing a process.

A hibernaculum may be subject to the following functions:

15 Int Usurp(Hibernaculum h, OverrideFlags f) copies the data and program modules of the process within h into the calling process's operating environment. Where there is a conflict between the data and/or program modules of the hibernaculum and the operating environment, the override flags specify which to preserve. Fig.5 is a flow-chart illustrating the steps of the usurp operation.

20 Int Bequeath(Hibernaculum h, Thread threadname, OverrideFlags f), upon threadname's termination, activates the threads of the process stored within h and runs them as threads within the environment of the process containing threadname. Where there is a conflict between the data and/or program modules of the hibernaculum and the calling process,  
25 the override flags specify which is to be preserved. Fig.6 is a flow-chart illustrating the steps of the bequeath operation.

Int Mutate(Stack s, int sFlag, Module m, int mflag, Data d, int dflag) modifies the  
30 execution state, program table and data heap of the calling process. If a thread has an entry in s, only the range of execution frames specified by this entry is preserved, the

other frames are discarded. Execution stacks belonging to threads without an entry in s are left untouched. In addition, program modules listed in m and data items listed in d are kept or discarded depending on the flag status. Fig.4 is a flow-chart illustrating the steps of the mutate operation.

5 In the following exemplary embodiment of the invention we shall assume that a user of a computing device is about to leave his machine and wishes to remove parts of a process to secondary or tertiary storage, while retaining enough of the data, program code and execution states to manage and respond to events on resources (eg network sockets and data locks) that are shared with the external world (eg other processes). Removing temporarily unwanted sub-processes frees up resources for other processes and/or users.

10 In the example that follows a number of operations that act upon a process are invoked by the process. These operations are Construct, Mutate, Usurp and Bequeath. Before describing the example in detail these operations – which are schematically illustrated in Fig.2 - will be discussed.

15 New processes are created with a Construct 110 operation. Fig.3 is a flow-chart showing the steps of this Construct operation. Each invocation of this operation starts up a controller thread in the process 230. The controller thread freezes all other active threads in the process 230, then creates a new process with some or all of the execution state, program modules and/or data of the process 230 except for those belonging to the controller thread, before resuming the frozen threads. Therefore, the new process contains  
20 no trace of the controller thread. The new process is suspended immediately and returned in a hibernaculum in the data area of the process 230. As explained earlier, a hibernaculum is a special data type that serves the sole purpose of providing a container for a suspended process. Since a process may have several hibernacula in its data area, it  
25 could create a new hibernaculum that contains those hibernacula, each of which in turn could contain more hibernacula, and so on. When the new process is activated subsequently, only those threads that were active just before the Construct 110 operation will begin to execute initially; threads that were suspended at that time will remain suspended. At the end of the Construct 110 operation, the controller thread resumes those  
30 threads that were frozen by it before terminating itself.

To specify what execution state should go into the new process, the Construct 110 operation is passed a list of ranges of context frames. The list may include frames from the state of several threads. No thread is allowed to have more than one range in this list. A thread can specify that all of its frames at the time of the Construct 110 operation are to be included in the list, by calling the AllFrame function beforehand. Alternatively, the thread can call the OpenFrame function to register its current frame, so that all the frames from the registered frame to the current frame at the time of the Construct 110 operation are included in the list. The thread can also call the CloseFrame function subsequently, to indicate that only frames from that registered with OpenFrame to the current frame at the time of calling CloseFrame are to be included in the list for the Construct 110 operation. An AllFrame or OpenFrame request for a thread erases any previous AllFrame, OpenFrame and CloseFrame requests for that thread. A CloseFrame request overrides any earlier CloseFrame request for the same thread, but the request is invalid if the thread has not already had an OpenFrame request. A thread can also make AllFrame, OpenFrame and/or CloseFrame requests on behalf of another thread by providing the identity of that thread in the requests; the effect is as if that thread is making those requests itself.

The Construct 110 operation can also be passed a list of program modules that should go into the newly created process. A thread can specify that all modules of the process 230 are to be included in the list, by calling the AllModules function prior to the Construct 110 operation. Alternatively, the thread can call the AddModule function to add a specific module to the list, and the DelModule function to remove a specific module from the list. The effect of the AllModules, AddModule and DelModule requests, possibly made by different threads, are cumulative. Hence a DelModule request after an AllModules request would leave every module in the list except for the one removed explicitly, and a DelModule can be negated with an AddModule or AllModules request. As there could be multiple AddModule requests for the same module and AllModules could be called multiple times, a program module may be referenced several times in the list. However, the Construct 110 operation consolidates the entries in the list, so no program module gets duplicated in the new process.

To copy some or all of the data of the process 230 to the new process, the Construct 110 operation can be passed a data list. This list contains only the name of, or reference to data that should be copied. The actual data content or values that get copied to the new process are taken at the time of the Construct 110 operation, not at the time that each datum is added to the list. To ensure consistency among data that could be related to each other, all the threads in the process 230 are frozen during the Construct 110 operation. A thread can specify that all data of the process 230 are to be included in the list, by calling the AllData function prior to the Construct 110 operation. Alternatively, the thread can call the AddDatum function to add a specific datum to the list, and the DelDatum function to remove a specific datum from the list. The effect of the AllData, AddDatum and DelDatum requests, possibly made by different threads, are cumulative. Hence a DelDatum request after an AllData request would leave all of the data in the list except for the one removed explicitly, and a DelDatum can be negated with an AddDatum or AllData request. As there could be multiple AddDatum requests for the same datum and AllData could be called multiple times, a datum may be referenced several times in the list. However, the Construct 110 operation consolidates the entries in the list, so no datum gets duplicated in the new process.

Since the lists passed to the Construct 110 operation are constructed from the execution state, program modules and data of the process 230, the new process initially does not contain any component that is not found in the process 230. Consequently, the symbol table in the new process is a subset of the symbol table of the process 230. Threads in the process 230 that do not have any frame in the new process are effectively dropped from it. For those threads that have frames in the new process, when activated later, each will begin execution at the instruction indicated by the program counter in the most recent frame amongst its frames that are copied. By excluding one or more of the most recent frames from the new process, the associated thread can be forced to return from the most recent module invocations. An exception is raised to alert the thread that those modules are not completed normally. Alternatively, the thread can be made to redo those modules upon activation, by decrementing the program counter in the most recent frame amongst those frames belonging to that thread that are copied. Similarly, by

excluding one or more of its oldest frames from the new process, a thread can be forced to terminate directly after completing the frames that are included.

The process 230 can also modify any of its components directly by calling the Mutate 180 operation from any thread. Fig.4 shows the flow-chart for the Mutate operation. The operation starts up a controller thread in the process 230. The controller thread first freezes all other active threads in the process 230, then selectively retains or discards its execution state, program modules and data. A list of context frames, together with a flag, can be passed to the Mutate 180 operation to retain or discard the frames in the list. Similarly, a program module list and/or a data list can be provided to indicate program modules and data of the process 230 that should be retained or discarded. The generation of the execution state, program module and data lists are the same as for the Construct 110 operation. After mutation, the controller thread resumes the threads that were frozen by it before terminating itself. Threads that no longer have a context frame in the process 230 are terminated. Each of the remaining threads resumes execution at the instruction indicated by the program counter in the most recent frame amongst the retained frames belonging to that thread. By discarding one or more of its most recent frames, a thread can be forced to return from the most recent module invocations. An exception is raised to alert the thread that those modules are not completed normally. Similarly, by discarding one or more of its oldest frames, a thread can be forced to terminate directly after completing the frames that are retained. Space freed up from the discarded context frames, program modules and data is automatically reclaimed by a garbage collector.

The Usurp 150 operation, which also accepts a hibernaculum as input, enables the process 230 to take in only program modules and data from a hibernaculum, without acquiring its threads. Fig.5 is a flow-chart showing this operation in detail. The operation starts up a controller thread in the process 230. The controller thread freezes all other active threads in the process 230, adds the program modules and data of the process in the hibernaculum to the program modules and data of the process 230, respectively, and updates its symbol table accordingly. In case of a name conflict, the program module or data from the hibernaculum is discarded in favor of the one from the process 230 by default. However, a flag can be supplied to give preference to the hibernaculum. Finally,

all the original threads in the process 230 that were frozen by the controller thread are resumed before it terminates itself.

The Bequeath 160 operation accepts a hibernaculum and a thread reference as input. Fig.6 is a flow-chart showing this operation in detail. It starts up a bequeath-thread in the process 230. The bequeath-thread registers the referenced thread and any existing bequeath-threads on that thread, then allows them to carry on execution without change. After all those threads and threads that they in turn activate have terminated, the bequeath-thread loads in the context frames, program modules and data in the hibernaculum. In case of a name conflict, the program module or data from the hibernaculum is discarded in favor of the one from the process 230 by default. However, a flag can be supplied to give preference to the hibernaculum. Subsequently, threads within the hibernaculum are activated to run in the process 230 before the bequeath-thread terminates itself. Only those threads that were active just before the hibernaculum was created are activated initially; threads that were suspended at that time remain suspended. Each newly acquired thread begins execution at the instruction indicated by the program counter in the most recent frame amongst the context frames that belong to that thread. If multiple Bequeath 160 requests are issued for the same thread, there will be several bequeath-threads in the process 230. Each bequeath-thread will wait for all the existing bequeath-threads on the same thread, together with all the threads that they activate, to terminate before performing its function. As a result, the Bequeath 160 requests are queued up and serviced in chronological order.

A process stored in a hibernaculum may also be transmitted to another device (for example a storage device) by the Send operation 120 and similarly may be received by the receive operation 130.

To begin the process p1 that is to be split calls the function Hibernaculum Construct:

Hibernaculum h = Construct(Stack s, Module m, Data d)

where s, m, and d contain the execution stacks, program modules and data, respectively, in process p1 that are not required in order to respond to events on shared

resources. This function creates a new process p2 to hold those heap, program table and execution states. The new process p2 is immediately suspended and returned within a hibernaculum h.

This Hibernaculum Construct operation is shown in the flowchart of Fig.3 and the  
5 result is a construct that holds the temporarily non-required sub-process.

The process p1 then calls the mutate function:

Int Mutate(Stack -s, Module -m, Data -d)

10 which discards from p1 the execution stacks, program modules and data specified in s, m and d respectively (ie the data held in the hibernaculum h). As a result p1 now holds only those data, program modules and execution states of the original process that are needed to respond to events on shared resources. It should be noted that the mutated process retains the same process identity, ie p1, as the original process. This mutate operation is  
15 shown in the flowchart of Fig.4. It should be noted here that while in this embodiment the first or active process retains the process identity of the original process, this is not essential and in an alternative the Construct operation can be used to generate a first process having a new process identity.

The mutated process p1 loads in appropriate event handling modules, then waits  
20 for incoming events. As p1 executes, the process may load in additional program modules, or may acquire data, program modules or execution states from the dormant process p2 using the function:

Int Usurp(Hibernaculum h, Stack s, Module m, Data d)

25 to take in from p2, which resides in the hibernaculum h, the execution stack, the program modules and data specified by s, m and d (and which may be a subset of those parameters held in the hibernaculum h). The usurp operation is shown in the flowchart of Fig.5.

When the user returns to the machine and wishes to restore the original process  
30 the mutated process p1 calls the function:



Int Mutate(Stack s, Module m, Data d)

where s, m and d contain the execution stacks, program modules and data that must be passed back to the original process. This discards any extraneous data, program code  
5 and/or execution states loaded in the user's absence.

Next p1 calls the function:

Int Bequeath(Hibernaculum h)

10 and quits. This results in all the execution stacks, program modules and data remaining in p1 being added to the dormant process p2 in the hibernaculum, and in p2 then being activated when p1 terminates. The Bequeath operation is shown in the flowchart of Fig.6.

It should also be understood that the dormant process p2 while held in the hibernaculum h could, if desired, be transmitted to another device such as a memory  
15 storage device, by using the Send operation 120. The dormant process p2 will then be re-transmitted and received using the receive operation 130 prior to the dormant process p2 being reattached to the original process. This would allow the memory capacity of the original device to be fully utilised by not requiring it to store dormant processes which may instead be stored offline.

20 It will also be understood that while in the above embodiment the first process is described as an active process and the second as a dormant process at least part of which may be reacquired by the active process later, the second process may alternatively comprise data, program code and execution states that are to be permanently deleted from the computing process as they are no longer required.

25 To implement the method of detaching and reattaching processes of the present invention in a Java environment, a package called snapshot is introduced. This package contains the following classes, each of which defines a data structure that is used in the operations involved in the method:

```
public class Hibernaculum {  
    ...  
}  
  
5 public class State {  
    ...  
}  
  
public class Module {  
10     ...  
}  
  
public class Data {  
    ...  
15 }  
  
public class Machine {  
    ...  
}  
20
```

In addition, the package contains a Snapshot class that defines the migration and adaptation operations:

```
public class Snapshot {  
25     private static native void registerNatives();  
    static {  
        registerNatives();  
    }  
  
30     public static native Hibernaculum Construct(State s, Module m, Data d);  
    public static native int Send(Hibernaculum h, OutputStream o);
```

```

public static native Hibernaculum Receive(InputStream i);
public static native int Usurp(Hibernaculum h, int f);
public static native int Bequeath(Hibernaculum h, int f);
public static native int Mutate(State s, Module m, int mflag, Data d, int dflag);

```

5

```

// This class is not to be instantiated
private Snapshot() {
}

```

10 }

The methods in the Snapshot class can be invoked from application code. For example:

```

15      try {
            if (snapshot.Snapshot.Construct(s, m, d) != null) {
                // hibernaculum has been created
            } else {
                // failed to create hibernaculum
20      }
            catch(snapshot.SnapshotException e) {
                // Failed to create hibernaculum
            }

```

25       The operations are implemented as native codes that are added to the Java virtual machine itself, using the Java Native Interface (JNI). To do that, a Java-to-native table is first defined:

```

#define KSH "Ljava/snapshot/Hibernaculum;"
30 #define KSS "Ljava/snapshot/State;"
#define KSM "Ljava/snapshot/Module;"

```

```
#define KSD "Ljava/snapshot/Data;"
```

```
static JNINativeMethod snapshot_Snapshot_native_methods[] = {
```

```
{
```

5

```
    "Construct",
```

```
    ("("KSSKSMKSD")"KSH,
```

```
    (void*)Impl_Snapshot_Construct
```

```
},
```

```
{
```

10

```
    "Send",
```

```
    ("("KSH"Ljava/io/OutputStream;)I",
```

```
    (void*)Impl_Snapshot_Send
```

```
},
```

```
{
```

15

```
    "Receive",
```

```
    ("("LJava/io/InputStream;)KSH,
```

```
    (void*)Impl_Snapshot_Receive
```

```
},
```

20

```
{
```

```
    "Usurp",
```

```
    ("("KSH"I)I",
```

```
    (void*)Impl_Snapshot_Usurp
```

```
},
```

25

```
{
```

```
    "Bequeath",
```

```
    ("("KSH"I)I",
```

```
    (void*)Impl_Snapshot_Bequeath
```

```
},
```

30

```
{
```

```

        "Mutate",
        ("("KSSKSM"l"KSD"l)"I",
        (void*)Impl_Snapshot_Mutate
    },
5
};

```

After that, the native implementations are registered via the following function:

```

10 JNIEXPORT void JNICALL
   Java_snapshot_Snapshot_registerNatives(JNIEnv *env, jclass cls) {
        (*env)->RegisterNatives(    env,
                                   cls,
                                   snapshot_Snapshot_native_methods,
15                                   sizeof(snapshot_Snapshot_native_methods) /
                                   sizeof(JNINativeMethod)    );
    }

```

Besides the above native codes, several functions are added to the Java virtual  
20 machine implementation, each of which realizes one of the migration and adaptation  
operations:

```

void* Impl_Snapshot_Construct(..) {
    // follow flowchart in Figure 3
25    ...
}

void* Impl_Snapshot_Send(..) {
    // send given hibernaculum to specified target
30    ...
}

```

```
void* Impl_Snapshot_Receive(..) {  
    // receive a hibernaculum from a specified source  
    ...  
5 }  

```

```
void* Impl_Snapshot_Usurp(..) {  
    // follow flowchart in Figure 5  
10    ...  
    }  

```

```
void* Impl_Snapshot_Bequeath(..) {  
    // follow flowchart in Figure 6  
15    ...  
    }  

```

```
void* Impl_Snapshot_Mutate(..) {  
20    // follow flowchart in Figure 4  
    ...  
    }  

```

25

30

CLAIMS

1. A method for removing a part of a computing process, wherein said process splits into a first process and a second sub-process, the second sub-process comprising items of data and/or program code and/or execution states of said computing process not required by said first process.
2. A method as claimed in claim 1 wherein said sub-process comprises items of data, program code and execution state of said computing process.
3. A method as claimed in claim 1 or 2 wherein a construct is formed for storing said sub-process, while said first process retains the process identity of said computing process.
4. A method as claimed in claim 3 wherein said construct is formed by a construct operation that suspends all active threads of said computing process and creates a new sub-process comprising at least some of the data and/or program modules and/or execution state of said computing process, and stores said sub-process in a data area of said computing process.
5. A method as claimed in claim 4 wherein said construct comprises only data, program modules and execution state falling within lists that are passed to said construct operation.
6. A method as claimed in any of claims 3 to 5 wherein said construct is provided with an authorising signature.
7. A method as claimed in any of claims 3 to 6 wherein said construct is sent to a memory storage device.

8. A method as claimed in any of claims 3 to 7 wherein said sub-process is a dormant process comprising data, program code and execution states of said computing process temporarily not required by said first process, and wherein said first process is able to re-acquire data, program codes and execution states from said dormant process as and when required by said first process.

9. A method as claimed in claim 8 wherein said first process re-acquires data, program code and execution states from said dormant process falling within specified ranges.

10. A method as claimed in claim 8 or 9 wherein said sub-process comprises data, program code and execution states specific to a given user of a computing means, and wherein said second process is formed to temporarily store said data, program code and execution states while said user is absent from said computing means.

11. A method as claimed in any of claims 3 to 10 wherein after said first process finishes executing data, program modules and execution states from said first process are added to said sub-process and said sub-process is reactivated.

12. A method as claimed in claim 11 wherein said first process discards extraneous data, program codes and execution states acquired subsequent to the formation of said first process and said sub-process prior to adding said first process to said sub-process.

13. A method as claimed in claim 1 or 2 wherein a construct is formed for storing said sub-process, while said first process is run in place of said computing process.

14. A method as claimed in claim 13 wherein said construct is formed by a construct operation that suspends all active threads of said computing process and creates a sub-process comprising at least some of the data and/or program modules and/or execution state of said computing process, and stores said sub-process in a data area of said first process.



15. A method as claimed in claim 14 wherein said construct comprises only data, program modules and execution state falling within lists that are passed to said construct operation.

5

16. A method as claimed in any of claims 13 to 15 wherein said construct is provided with an authorising signature.

17. A method as claimed in any of claims 13 to 16 wherein said construct is sent to a memory storage device.

10

18. A method as claimed in any of claims 13 to 17 wherein said sub-process is a dormant process comprising data, program code and execution states of said computing process temporarily not required by said first process, and wherein said first process is able to re-acquire data, program codes and execution states from said dormant process as and when required by said first process.

15

19. A method as claimed in claim 18 wherein said first process re-acquires data, program code and execution states from said dormant process falling within specified ranges.

20

20. A method as claimed in claim 18 or 19 wherein said sub-process comprises data, program code and execution states specific to a given user of a computing means, and wherein said sub-process is formed to temporarily store said data, program code and execution states while said user is absent from said computing means.

25

21. A method as claimed in any of claims 13 to 20 wherein after said first process finishes executing data, program modules and execution states from said first process are added to said sub-process and said sub-process is reactivated.

30

22. A method as claimed in claim 21 wherein said first process discards extraneous data, program codes and execution states acquired subsequent to the formation of said first process and said sub-process prior to adding said first process to said sub-process.

5

10


15

20

25

30

1/6

**Fig.1**

2/6




Fig.2

3/6




Fig.3

4/6




Fig.4

5/6




Fig.5

6/6




Fig.6



## Declaration and Power of Attorney For Utility or Design Patent Application English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

A Method Of Detaching And Re-Attaching Components Of A Computing Process

the specification of which is attached hereto unless the following box is checked:

☒ was filed on 22 February 1999 as

United States Application Number \_\_\_\_\_ (if applicable) or,  
and was amended on \_\_\_\_\_

PCT International Application Number PCT/SG99/00009  
and was amended on \_\_\_\_\_ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119 (a-d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designated at least one country other than the United States of America, listed below. I have also identified below, by checking the "No" box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed:

PCT/SG98/00102 (Number)	WO (Country)	16 DECEMBER 1998 (Day/Month/Year Filed)	Priority Claimed	
			<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No

☐ Additional foreign application numbers are listed on a supplemental priority sheet attached hereto.

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

_____ (Number)	_____ (Day/Month/Year Filed)
_____ (Number)	_____ (Day/Month/Year Filed)
_____ (Number)	_____ (Day/Month/Year Filed)

☐ Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

(Application No.)

(Filing Date)

(Status)

(patented, pending, abandoned)

(Application No.)

(Filing Date)

(Status)

(patented, pending, abandoned)

☐ Additional U.S. or international application numbers are listed on a supplemental priority sheet attached hereto.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

The undersigned hereby authorizes the U.S. attorney or agent named herein to accept and follow instructions from either his foreign patent agent or corporate representative, if any, as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. attorney or agent named herein will be so notified by the undersigned.

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the attorney(s) and/or agent(s) associated with the Customer Number provided below to prosecute this application and transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to that Customer Number:

**CUSTOMER NUMBER 7055**

The appointed attorneys include:

Neil F. Greenblum Reg. No. 28,394  
Bruce H. Bernstein Reg. No. 29,027  
Arnold Turk Reg. No. 33,094  
James L. Rowland Reg. No. 32,674

Stephen M. Roylance Reg. No. 31,296  
Leslie J. Paperner Reg. No. 33,329  
William Pieprz Reg. No. 33,630  
William E. Lyddane Reg. No. 41,568

At: Greenblum & Bernstein, P.L.C.  
1941 Roland Clarke Place  
Reston, VA 20191

Direct Telephone Calls to: Greenblum & Bernstein, P.L.C. (703) 716-1191

1-00  
Full name of sole or first inventor

PANG Hwee Hwa (Family name PANG)

Inventor's signature



Date

11 June 2001

Residence

Singapore

JPX

Citizenship


Singapore

Post Office Address

201 Tanjong Rhu Road #15-11, Singapore 439617

(Supply similar information and signature for second and subsequent joint inventors.)

2-00

Full name of second joint inventor, if any	NGAIR Teow Hin	(Family name Ngair)
Second Inventor's signature		Date 11 June 2001
Residence	<u>Singapore</u>	99X
Citizenship	Singapore	
Post Office Address	334 Kang Ching Road #13-254, Singapore 610334	
Full name of third joint inventor, if any		
Third Inventor's signature		Date
Residence		
Citizenship		
Post Office Address		
Full name of fourth joint inventor, if any		
Fourth Inventor's signature		Date
Residence		
Citizenship		
Post Office Address		
Full name of fifth joint inventor, if any		
Fifth Inventor's signature		Date
Residence		
Citizenship		
Post Office Address		